## **CYCLE 2018-07**

Sorting order:

A – first 'quotas', then 'suspensions'

B – **new** requests, **amending** requests

>>>The duty suspension and quota requests on the following list are currently under discussion. The data available on this list may not represent the final state of the discussions within the relevant Commission Working group.

Please note that it cannot be guaranteed that the information available exactly reproduces an officially adopted text. Only European Union legislation published in the Official Journal of the European Union is deemed authentic<<<

CN code	TARIC	Reference Mail	Description	S/Q	New or amendme nt request	Measure status	Partner Position Country	Partner Position	Public Comments
2915 90 70		4419073/2017	Ethyl 2,2,2-trifluoroacetate (CAS RN 383-63-1)	Q/200000kg, 01.07-31.12	New	UNDER EXAMINATION	IT	Applicant	Round 2018-07 Ethyl 2,2,2-trifluoroacetate -Used in the synthesis of pharmaceutical intermediates and active pharmaceutical ingredients
2909 41 00		4503739/2017	2,2' – Oxydiethanol (diethylene glycol, digol) (CAS RN 111-46-6)	Q/2250tonnes, 01.07-31.12	New	UNDER EXAMINATION	IT	Applicant	Round 2018-07 2,2' – Oxydiethanol (diethylene glycol, digol) (CAS RN 111-46-6) The use of the finished or semi-finished products:DEG to manufacture polymers (resins for coating)
2914 19 90		4615801/2017	Acetylacetone for the production of calcium acetylacetonat (CAS RN 123-54-6)	Q/550tonnes, 01.07-31.12	New	UNDER EXAMINATION	TR	Applicant	Round 2018-07 Raw material used for Calcium Asetil Asetonat
2309 90 31		4693681/2017	Soya Bean Protein Concentrate containing by weight:  - 60 % (± 10 %) of crude protein,  - 5 % (± 3 %) of crude fibre, and  - 5 % (± 3 %) of crude ash	Q/15000tonnes , 01.07-31.12	New	UNDER EXAMINATION	UK	Applicant	Round 2018-07  As an ingredient for animal feed

		[for use in the manufacture of products of food and drink industry (1)]						
2910 30 00	4509767/2017	1-Chloro-2,3-epoxypropane (epichlorohydrin)	Q/10500000kg, 01.07-31.12	New	UNDER EXAMINATION	DE	Applicant	Round 2018-07 Raw material for the production of epoxy resin Use as a monomer in polymer production
7409 19 00	4537627/2017	Copper plate or sheet having a thickness of more than 0.15 mm but not more than 0.3 mm on plates or sheets of an aluminum nitride or silicon nitride ceramic	Q/3500000piec es, 01.07-31.12	New	UNDER EXAMINATION	DE	Applicant	Round 2018-07 The product is used as a circuit board for the production of IGBT modules
2906 11 00	4573475/2017	Natural levomenthol (INN) CAS RN 2216-51-5)	Q/kg, 01.07- 31.12	New	UNDER EXAMINATION	DE DE	Applicant Opposed	Round 2018-07 Production of natural flavours or aromatising of food, cosmetics, pharmaceuticals, animal food
2933 39 99	4637024/2017	Fluazinam (ISO) (CAS RN 79622-59-6), with a purity by weight of 98,5 % or more	Q/100000kg, 01.07-31.12	New	UNDER EXAMINATION	FR	Applicant	Round 2018-07 Fungicide
2905 31 00	296972/2011 4545921/2017 5555215/2016	Mono Ethylene glycol (ethanediol) (CAS RN 107-21-1)	Q/350000tonn es, 01.07-31.12	Amendment	UNDER EXAMINATION	LT TR BE DE DE ES FR	Applicant Applicant Opposed Opposed Opposed Opposed Opposed	Round 2018-07: NEW request was transferred in request for amendment, to keep the history of this file since it was discussed several times
ex 3811 29 00 55	826457/2014	FR- Request for amendment: Additives consisting of reaction products of diphenylamine and branched nonenes with: - by weight more than 28 %, but not more than 35 % of 4-	Q/900tonnes, 01.01-31.12	Amendment	UNDER EXAMINATION	FR DE	Applicant Opposed	ROUND 2018-07 –Request for amendment in text description Round 2018-01 Objected. Transferred into Quota

	monononyldiphenylamine, and - by weight more than 50 % but not more than 65 % of 4,4'- dinonyldiphenylamine, - by weight a total percentage of 2, 4-dinonyldiphenylamine and 2, 4'- dinonyldiphenylamine of not more than 5 %, used for the manufacture of lubricating oils						
	Additives consisting of reaction products of diphenylamine and branched nonenes with:  - by weight more than 28 %, but not more than 35 % of 4-monononyldiphenylamine, and - by weight more than 50 % but not more than 65 % of 4,4'-dinonyldiphenylamine, - by weight a total percentage of 2, 4-dinonyldiphenylamine and 2, 4'-dinonyldiphenylamine of not more than 5 %, used for the manufacture of lubricating oils (1)						
7202 30 00 1653260	Ferrosilicomanganese, containing by weight:  - 45 % or more of manganese (Mn)  - 2.50 % or less of carbon (C)  - 10 % or more of silicon (Si)  - 0.60 % or less of phosphorus (P)  - 0.15 % or less of sulphur (S)	Q/110000tonn es, 01.01-31.12	Amendment	UNDER EXAMINATION	TR ES EU EU FR SK	Applicant Opposed Opposed Opposed Opposed Opposed	Round 2018-07 – rolled over as a request for TR national quota Round 2018-01- Objected as suspension request  Ferrosilicomanganese Inserted to steel as alloying element and it increases quality of the steel. And is finally used for steel bar, wire rod, steel billet production.

7202 21 00		1653227/2017	Ferro-silicon containing by weight 55 % more or more but not more than 80 % of silicon	Q/50000tonnes , 01.01-31.12	Amendment	UNDER EXAMINATION	TR ES EU EU FR SK	Applicant Opposed Opposed Opposed Opposed Opposed	Round 2018-07- rolled over as a request for TR national quota Round 2018-01- Objected as suspension request  Ferrosilicon (including silicon more than %55 but less than %80) Inserted to steel as alloying element and it increases quality of the steel and also used for deoxidant purpose. And is finally used for steel bar, wire rod, steel billet production.
ex 2921 41 00	10	816326/2014	Aniline with a purity by weight of 99 % or more (CAS RN 62-53-3)	Q/150000tonn es, 01.01-31.12	Amendment	UNDER EXAMINATION	HU SK BE DE DE	Applicant Applicant Opposed Opposed Opposed	Round 2018-07 - request for increase ROUND 2015-01 Production of MDI products (methylene-diphenyl-diisocyanates)
8104 11 00		1/1/1994	Unwrought magnesium, containing at least 99,8 % by weight of magnesium	Q/90000tonnes , 01.01-31.12	Amendment	UNDER EXAMINATION	FR BE DE UK TR	Applicant Co-applicant Co-applicant Co-applicant Opposed	Round 2018-07 – rolled over from the previous round ROUND 2017-01:Objection to the running measure  Prolongation Exercise 1/1/2014 + 09.2744 JO L 304 du 29.11.94
ex 3204 17 00	14	647206/2014	Preparations based on Colourant C.I. Pigment Red 48:2 (CAS RN 7023-61- 2) with a content thereof of 60 % or morebut less than 85 % by weight	Q/50tonnes, 01.01-31.12	Amendment	UNDER EXAMINATION	UK	Applicant	Round 2018-07 - description should be amended to avoid overlap with sus ex 3204 17 00 19  ROUND 2015-01-01  Colourant used in the manufacture of printing inks and in the colouration of other plastic, paint and rubber products
ex 8504 40 82	30	165476/2010	Power supply boards for use in the manufacture of goods falling under heading 8521 and 8528 (1)	Q/15000000pie ces, 01.01- 31.12	Amendment	UNDER EXAMINATION	PL PL	Applicant Opposed	Round 2018-07- Request for increase

ex 5906 99 90	20	1361569/2016	ROUND 2018-7	Q/375000m <sup>2</sup> ,	Amendment	UNDER	HU	Applicant	ROUND 2018-7 :Request for
			HU proposed amendement:	01.01-31.12		EXAMINATION	AT	Opposed	amendment
			Woven and laminated rubberised textile						ROUND 2017 01:The imported
			fabric with the following characteristics:						rubberised textile fabric is a component
			- with three layers,						of the outer layer of the retractable roof
			- one outer layer consists of acrylic						of motor vehicles
			fabric,						
			- the other outer layer consists of						
			polyester fabric,						
			- the middle layer consists of						
			chlorobutyl rubber,						
			- the middle layer has a weight of						
			452 g/m2 or more but not more than						
			569 g/m2 ,						
			- the textile fabric has a total weight						
			of 952 g/m2 or more but not more						
			than 1 159 g/m2,						
			- the textile fabric has a total						
			thickness of 0,8 mm or more but not						
			more than 4 mm,						
			used for the manufacture of the						
			retractable roof of motor vehicles						
			Current description:						
			Woven and laminated rubberised textile						
			fabric with the following characteristics:						
			- with three layers,						
			<ul> <li>one outer layer consists of acrylic</li> </ul>						
			fabric,						
			- the other outer layer consists of						
			polyester fabric,						
			- the middle layer consists of						
			chlorobutyl rubber,						
			- the middle layer has a weight of						
			486 g/m <sup>2</sup> or more but not more than						
			569 g/m <sup>2</sup> ,						
			- the textile fabric has a total weight						
			of 952 g/m <sup>2</sup> or more but not more than						
			$1159 \text{ g/m}^2$ ,						
I			<ul> <li>the textile fabric has a total</li> </ul>			1			

		thickness of 0.8 mm or more but not more than 4 mm, used for the manufacture of the retractable roof of motor vehicles (1)						
2912 42 00	1927/2/2003	Ethylvanillin (3-ethoxy-4-hydroxybenzaldehyde) (CAS RN 121-32-4)	Q/1950tonnes, 01.01-31.12	Amendment	UNDER EXAMINATION	FR AT	Applicant Co-applicant	Round 2018-07 - request for increase pour aliments et parfums
2926 10 00	910/2006	Acrylonitrile (CAS RN 107-13-1)	Q/75000tonnes , 01.07-31.12	Amendment	UNDER EXAMINATION	TR BE DE FR NL	Co-applicant	Round 2018-07 - Request for increase ROUND 01-2016 objection - run-down of quota

CN code	TARIC	Reference Mail	Description	S/Q	New or amendment request	Measure status	Partner Position Country	Partner Position	Public Comments
0910 99 99		4656721/2017	Celery seed ( <i>Apium graveolens</i> ) in ground form, with a gluten level of less than 20 parts per million [for use in the manufacture of products in food and drink industry (1)]	S	New	UNDER EXAMINATION	UK	Applicant	Round 2018-07  For use as an ingredient flavouring in commercial sauces, seasonings, spices and salad accompaniments
2106 90 92		4639141/2017	Preparation containing by weight:  - 15 % or more but not more than 35 % of buttermilk  - 20 % (+/-10 %) of lactose  - 20 % (+/-10 %) of whey protein concentrate  - 20 % (+/-10 %) of cheddar cheese  - 3 % (+/-2 %) of salt  - 0.1 % or more but not more than 10 % of lactic acid E270  - 0.1 % or more but not more than 10 % of gum arabic E414	S	New	UNDER EXAMINATION	UK AT	Applicant Opposed	Round 2018-07 for use in the manufacture of products of food and drink industry

		for use in the manufacture of products of food and drink industry (1)						
2712 90 99	4509576/2017	Mixture of 1-alkenes (alpha-olefins) having even numbered count of carbon atoms and a chain length of 24 to 64 carbon atoms, the main component having 30 or more carbon atoms	S	New	UNDER EXAMINATION	DE	Applicant	Round 2018-07  Use as a recipe component in wax emulsions
2842 10 00	4509652/2017	Fluorphlogopite (CAS RN 12003-38-2)	s	New	UNDER EXAMINATION	DE	Applicant	Round 2018-07
								Use as a color pigment and as a base for coated pigments
2842 90 80	4509612/2017	Aluminum trititanium dodecachloride (CAS RN 12003-13-3)	s	New	UNDER EXAMINATION	DE	Applicant	Round 2018-07 Aluminum trititanium dodecachloride (CAS RN 12003-13-3)/ Polymerization catalyst, reagent for organic synthesis
2903 99 80	4489999/2017	1,1'-methanediylbis(4-fluorobenzene) (CAS RN 457-68-1)	s	New	UNDER EXAMINATION	UK	Applicant	ROUND 2018-07
								1,1'-methanediylbis(4-fluorobenzene) (CAS RN 457-68-1)
2905 29 90	4503810/2017	Cis-hex-3-en-1-ol (CAS RN 928-96-1)	s	New	UNDER EXAMINATION	UK AT	Applicant Co-applicant	Round 2018-07 Cis-hex-3-en-1-ol (CAS RN 928-96-1)/ Alcoholic perfumes & fragrances used in producing soaps, shampoos, shower gel, fabric softeners and liquid detergents
2906 29 00	4610103/2017	2,2'-(m-phenylene)dipropan-2-ol (CAS RN 1999-85-5)	s	New	UNDER EXAMINATION	NL	Applicant	ROUND 2018 2,2'-(m-phenylene)dipropan-2-ol (CAS RN 1999-85-5)
2907 29 00	4509689/2017	Biphenyl-4,4'-diol (CAS RN 92-88-6)	S	New	UNDER EXAMINATION	DE	Applicant	Round 2018-07- Biphenyl-4,4'-diol (CAS RN 92-88-

								6)//Preparation of polysulfones
2912 29 00	4509799/2017	p-Phenylbenzaldehyde (CAS RN 3218-36-8)	S	New	UNDER EXAMINATION	DE	Applicant	Round 2017-07- p-Phenylbenzaldehyde (CAS RN 3218- 36-8)
2912 49 00	4422644/2017	2,6-dihydroxybenzaldehyde (CAS RN 387-46-2)	s	New	UNDER EXAMINATION	ES	Applicant	ROUND 2018-07- 2,6-dihydroxybenzaldehyde (CAS RN 387-46-2)
2914 29 00	4632248/2017	2-sec-butylcyclohexanone (CAS RN 14765-30-1)	s	New	UNDER EXAMINATION	UK	Applicant	ROUND 2018 2-sec-butylcyclohexanone(CAS RN 14765-30-1)
2914 29 00	4503840/2017	1-(cedr-8-en-9-yl)ethanone (CAS RN 32388-55-9)	s	New	UNDER EXAMINATION	UK	Applicant	Round 2018-07 For the production of fragrances
2915 39 00	4491921/2017	M-phenylene diacetate (CAS RN 108-58-7) of a purity by weight of 98 % or more	s	New	UNDER EXAMINATION	UK	Applicant	ROUND 2018-07 For use in the production of power transmission belts
2915 39 00	4638366/2017	Cis-3-hexenyl acetate (CAS RN 3681-71-8)	s	New	UNDER EXAMINATION	UK	Applicant	Round 2018-07 For the production of fragrances
2915 39 99	4632314/2017	trans-4-tert-butylcyclohexyl acetate (CAS RN 32210-23-4)	S	New	UNDER EXAMINATION	UK	Applicant	ROUND 2018- trans-4-tert-butylcyclohexyl acetate (CAS RN 32210-23-4)
2915 59 90	4610274/2017	4,4'-methanediyldianiline (CAS RN 101-77-9)	S	New	UNDER EXAMINATION	AT	Applicant	ROUND 2018 4,4'-methanediyldianiline (CAS RN 101-77-9)
2915 90 70	4509828/2017	Methyl (R)-2-Fluoropropionate (CAS RN 146805-74-5)	s	New	UNDER EXAMINATION	DE	Applicant	Round 2018-07 Methyl (R)-2-Fluoropropionate (CAS RN 146805-74-5/ for the production of plant protection products

2916 12 00	4632366/2017	Ethyl (1S,2R,6R,7R)- tricyclo[5.2.1.0(2,6)]decane-2- carboxylate (CAS RN 80657-64-3) and its' isomer Ethyl (1R,2R,6R,7S)- tricyclo[5.2.1.0(2,6)]decane-2- carboxylate (CAS RN 80263-07-0)	S	New	UNDER EXAMINATION	UK	Applicant	Round 2018-07- For the production of fragrances
2918 30 00	4419266/2017	2-FLUORO-5-FORMYLBENZOIC ACID (CAS RN 550363-85-4)	s	New	UNDER EXAMINATION	IT	Applicant	ROUND 2018-07- 2-FLUORO-5-FORMYLBENZOIC ACID (CAS RN 550363-85-4)
2918 99 90	4488741/2017	2-[4-(2,4-dichlorophenoxy)phenoxy]propanoate (CAS RN 51338-27-3)	S	New	UNDER EXAMINATION	ES	Applicant	ROUND 2018-07- Organic chemicals used as active ingredient for the formulation of plant protection products
2922 39 00	4609918/2017	2-Amino-3,5-dibromobenzaldeide (CAS RN 50910-55-9)	S	New	UNDER EXAMINATION	IT	Applicant	ROUND 2018- 2-Amino-3,5-dibromobenzaldeide (CAS RN 50910-55-9)
2924 19 00	4418617/2017	Sodium 8-[(2-hydroxybenzoyl)amino]octanoate (Salcaprozic acid sodium salt)	S	New	UNDER EXAMINATION	DK	Applicant	ROUND 2018-07- Sodium 8-[(2- hydroxybenzoyl)amino]octanoate (Salcaprozic acid sodium salt)
2926 29 70	4632435/2017	2-Cyclohexylidene-2-phenylacetonitrile (CAS RN 10461-98-0)	s	New	UNDER EXAMINATION	UK	Applicant	Round 2018-07- For the production of fragrances
2926 90 70	4509883/2017	Flumethrin (ISO) CAS RN 69770-45-2)	s	New	UNDER EXAMINATION	DE	Applicant	Round 2018-07
2926 90 70	4509853/2017	Deltamethrin (ISO) (CAS RN 52918-63-5)	s	New	UNDER EXAMINATION	DE	Applicant	Round 2018-07- Deltamethrin (ISO) (CAS RN 52918- 63-5)
2927 00 00	4613845/2017	2,2'-azobis (4-methoxy-2,4-dimethylvaleronitrile) (CAS RN 15545-97-8)	S	New	UNDER EXAMINATION	BE	Applicant	ROUND 2018-07- 2,2'-azobis (4-methoxy-2,4-

								dimethylvaleronitrile) (CAS RN 15545-97-8)
2931 90 00	4422677/2017	(3-fluoro-5-isobutoxyphenyl)boronic acid (CAS RN 850589-57-0)	S	New	UNDER EXAMINATION	ES	Applicant	ROUND 2018-07- (3-fluoro-5-isobutoxyphenyl)boronic acid (CAS RN 850589-57-0)
2932 10 00	4656805/2017	Furfuryl Alcohol (CAS RN 98-00-0)	s	New	UNDER EXAMINATION	UK	Applicant	Round 2018-07-Used in thermoset polymer matrix composites, cements, adhesives, coatings and casting/foundry resins
2932 99 00	4636962/2017	2-ethyl-3-hydroxy-4-pyrone (CAS RN 4940-11-8)	s	New	UNDER EXAMINATION	UK AT	Applicant Co-applicant	2018-07- 2-ethyl-3-hydroxy-4-pyrone (CAS RN 4940-11-8)// For the production of fragrances
2933 39 90	4418874/2017	N-{[(2R)-2-hydroxy-3-piperidin-1-ylpropoxy}-1-oxipyridine-1-ium-3-carboximidoyl, citrate	s	New	UNDER EXAMINATION	DK	Applicant	ROUND 2018-07 Arimoclomol citrate is used in the research and development of new products
2933 39 99	4422468/2017	(2-chloropyridin-3-yl) methanol (CAS RN 42330-59-6)	s	New	UNDER EXAMINATION	ES	Applicant	ROUND 2018-07 (2-chloropyridin-3-yl) methanol (CAS RN 42330-59-6)
2933 39 99	4422608/2017	2,6-dichloropyridine-3-carboxiamide (CAS RN 62068-78-4)	s	New	UNDER EXAMINATION	ES	Applicant	ROUND 2018-07 2,6-dichloropyridine-3-carboxiamide (CAS RN 62068-78-4)
2933 39 99	4490035/2017	2,5 Dichloro-4,6-dimethylnictinonitrile (CAS RN 91591-63-8)	S	New	UNDER EXAMINATION	UK	Applicant	ROUND 2018-07 Used in the production of an active pharmaceutical ingredient
2933 59 95	4609879/2017	6-chloro-1,3-dimethyl-pyrimidine-2,4-dione (CAS RN 6972-27-6)	s	New	UNDER EXAMINATION	IT	Applicant	ROUND 2018 6-chloro-1,3-dimethyl-pyrimidine-2,4- dione (CAS RN 6972-27-6)

2933 59 95	4419296/2017	1-(Cyclopropylcarbonyl)piperazine Hydrochloride (CAS RN 1021298-67-8)	s	New	UNDER EXAMINATION	IT	Applicant	ROUND 2018-07 1-(Cyclopropylcarbonyl)piperazine Hydrochloride (CAS RN 1021298-67- 8)
2933 59 95	4546001/2017	5-Fluoro-4-hydrazino-2- methoxypyrimidine (CAS RN 166524- 64-7)	s	New	UNDER EXAMINATION	UK	Applicant	ROUND 2018 5-Fluoro-4-hydrazino-2- methoxypyrimidine (CAS RN 166524- 64-7)
2933 79 00	4419345/2017	Methyl 2-oxo-2,3-dihydro-1H-indole-6- carboxylate (CAS RN 14192-26-8)	s	New	UNDER EXAMINATION	IT	Applicant	ROUND 2018-07 Methyl 2-oxo-2,3-dihydro-1H-indole- 6-carboxylate (CAS RN 14192-26-8)
2933 99 80	4513002/2017	5-Amino-6-methyl-2-benzimidazolone (CAS RN 67014-36-2)	s	New	UNDER EXAMINATION	DE	Applicant	Round 2018-07
2934 99 90	4692977/2017	Dolutegravir (INN) (CAS 1051375-16-6) and their salts	s	New	UNDER EXAMINATION	SI	Applicant	ROUND 2018- Dolutegravir (INN) (CAS 1051375-16- 6) and their salts
2935 90 90	4692923/2017	Venetoclax (INN) (CAS 1257044-40-8)	S	New	UNDER EXAMINATION	SI	Applicant	Round 2018-07
3204 13 00	4546104/2017	Colourant C.I. Basic blue 41 (CAS RN 69852-41-1) and preparations based thereon with a colourant C.I. Basic blue 41 content of 50 % or more by weight	s	New	UNDER EXAMINATION	TR	Applicant	ROUND 2018- C.I. Basic blue 41 dye (CAS RN 69852-41-1)
3204 13 00	4546201/2017	Colourant C.I. Basic yellow 28 (CAS RN 54060-92-3) and preparations based thereon with a colourant C.I. Basic yellow 28 content of 50 % or more by weight	s	New	UNDER EXAMINATION	TR	Applicant	ROUND 2018 C.I. Basic yellow 28 dye (CAS RN 54060-92-3)
3204 13 00	4546154/2017	C.I. Basic red 46 dye (CAS RN 38845-47-5) and 20% or more by weight of C.I. Basic red 46 preparations	s	New	UNDER EXAMINATION	TR	Applicant	ROUND 2018 C.I. Basic red 46 dye (CAS RN 38845-47-5)

3204 13 00	4546229/2017	Colourant C.I. Basic blue mix (blue 3 and blue 159) (CAS RN MIX (33273-26-6, 81921-84-8))) and preparations based thereon with a colourant C.I. Basic blue mix (blue 3 and blue 159) content of 60 % or more by weight	S	New	UNDER EXAMINATION	TR	Applicant	ROUND 2018 C.I. Basic blue mix (blue 3 and blue 159) dye (CAS RN MIX (33273-26-6, 81921-84-8))
3204 16 00	4548665/2017	Colourant C.I. Reactive Red 141 (CAS RN 61931-52-0) and preparations based thereon with a colourant C.I. reactive Red 141 content of 13 % or more by weight	s	New	UNDER EXAMINATION	DE	Applicant	ROUND 2018 Colourant C.I. Reactive Red 141 (CAS RN 61931-52-0)
3204 17 00	4505704/2017	Colourant C.I. Pigment Red 268 (CAS RN 16403-84-2) and preparations based thereon with a Colourant C.I. Pigment Red 268 content of 80 % or more by weight	S	New	UNDER EXAMINATION	UK	Applicant	Round 2018-07 Colourant C.I. Pigment Red 268 (CAS RN 16403-84-2) and preparations based thereon with a Colourant C.I. Pigment Red 268 content of 80 % or more by weight
3206 49 70	4505654/2017	Colourant C.I. Pigment Blue 27 (CAS RN 25869-00-5) and preparations thereon with a Colourant C.I. Pigment Blue 27 content of 85 % or more by weight	S	New	UNDER EXAMINATION	UK	Applicant	Round 2018-07 Colourant C.I. Pigment Blue 27 (CAS RN 25869-00-5) and preparations thereon with a Colourant C.I. Pigment Blue 27 content of 85% or more by weight//Used in the manufacturing of pigments
3206 49 70	4638433/2017	Pigment preparation containing by weight:  - 85 % or more but not more than 93 % of silica (CAS RN 60676-86-0)  - 2 % or more but not more than 5.5 % of titanium(CAS RN 7440-32-6)  - 5 % or more but not more than 8.5 % of aluminium (CAS RN 7429-90-5)	S	New	UNDER EXAMINATION	UK	Applicant	Round 2018-7 For use in the manufacture of inks
3707 10 00	4613870/2017	Sensitising emulsion, containing: - not more than 5 % by weight of	s	New	UNDER EXAMINATION	BE	Applicant	ROUND 2018-07 Sensitising emulsion

		photoacid generator  - 2 % or more but not more than 50 % by weight of phenolic resins  - not more than 7 % by weight of epoxy-containing derivatives dissolved in heptan-2-one and/or ethyllactate						
3802 10 00	4565219/2017	Activated carbon in granular form with:  - a size of 8x35 or more but not more than 6x18 sieve stack,  - apparent Density of 0,2g/ml or more but not more than 0,4g/ml,  - with BWC (Butan Working Capacity) result of a minimum of 11 g butane/100ml,  - for vapor absorption and desorption used in fuel vapor absorbers in fuel systems of motor vehicles or in Pellet (cylindrical) form with:  - a diameter of 2mm or more but not more than 3 mm,  - with Apparent Density of 0,2g/ml or more but not more than 0,4g/ml,  - with BWC (Butan Working Capacity) result of a minimum of 5 g butane/100ml,  - for vapor absorption and desorption used in fuel vapor absorbers in fuel systems of motor vehicles		New	UNDER EXAMINATION	PL	Applicant	ROUND 2018 Activated Carbon in either: Granular form or Pellet (cylindrical) form
3804 00 00	4615750/2017	Sodium Lignosulphonate containing by weight 55 % or more of sodium lignosulphonate calculated on dry weight	s	New	UNDER EXAMINATION	TR	Applicant	ROUND 2018  Sodium Lignosulphonate containing by weight 55% or more of sodium lignosulphonate calculated on dry weight
3808 93 90	4628990/2017	Preparation in the form of uncoated tablets containing at least by weight	S	New	UNDER EXAMINATION	FR	Applicant	ROUND 2018

		0.55 % and no more than 2.50 % of 1-methylcyclopropene (1-MCP), n° CAS 3100-04-7 with a minimum purity by weight of 96 % and containing less than 0.05 % by weight of each of the two impurities, 1-chloro-2-methylpropene et 3-chloro-2-methylpropene						
3812 10 00	4656777/2017	Mixture of 2,2-Bis(4-hydroxyphenyl)- hexafluoropropane (CAS RN 1478-61-1), and Benzyl Triphenyl Phosphonium Salt (CAS RN 75768-65-9)	s	New	UNDER EXAMINATION	UK	Applicant	
3824 99 96	4537658/2017	Rare-earth concentrate containing by weight  - rare-earth oxides of 35 % or more but not more than 45 %,  - zirconium oxide not more than 65 % and  - having a loss on ignition of 5 % or more by weight	s	New	UNDER EXAMINATION	DE	Applicant	Round 2018-07 used in the production of car exhaust gas catalytic converters
3904 69 80	4537555/2017	Mixture of polytetrafluoroethylene (CAS RN 9002-84-0) and acrylonitrile-styrene copolymer (CAS RN 9003-54-7), each containing 50 % by weight [(+/- 1)]	s	New	UNDER EXAMINATION	DE	Applicant	Round 2018-07 Mixture of polytetrafluoroethylene (CAS RN 9002-84-0) and acrylonitrile- styrene copolymer (CAS RN 9003-54- 7), each containing 50% by weight [(+/- 1)]
3906 90 90	4422335/2017	High-functionality glycidyl acrylic polymers, in the form of ground flake with a maximum size of 1 cm, for powder coatings	s	New	UNDER EXAMINATION	IT	Applicant	ROUND 2018-07 High-functionality glycidyl acrylic polymers

3907 30 00	4573511/2017	Preparation of epoxy resin (CAS RN 29690-82-2) and phenolic resin (CAS RN 9003-35-47) containing  - by weight of 65 % or more but not more than 75 % silicon dioxide (CAS RN 60676-86-0)  - also not more than 0,5 % by weight of carbon black (CAS RN 1333-86-4)	S	New	UNDER EXAMINATION	DE	Applicant	Round 2018-07 Used in the manufacturing of semi- conductor components
3909 20 00	4573548/2017	Melamine resin (CAS RN 9003-08-1) containing by weight 60 % or more but not more than 75 % containing: - silica (CAS RN 14808-60-7 or 60676-86-0) with a content by weight of 15 % or more but not more than 25 %, - Cellulose (CAS RN 9004-34-6 5) with a content by weight of 5 % or more but not more than 15 %, and - phenolic resin (CAS RN 25917-04-8 1) with a content by weight of 1 % or more but not more than 15 %	S	New	UNDER EXAMINATION	DE	Applicant	Round 2018-07 Use in the transfermold process during the production of semiconductor components
3920 99 28	4537586/2017	Polyester film on roll with a thickness of 0.35 mm, coated with a gold layer with a strength of 0.03 $\mu$ m or more, but not more than 0.06 $\mu$ m	S	New	UNDER EXAMINATION	DE	Applicant	Round 2018-07 The plastic film is used for the production of test strips for the electrochemical measurement of the blood glucose values
3920 99 59	4656736/2017	Polytetrafluoroethylene film, with - a thickness of 50 μm but not more than 155 μm, - an elongation at break of not more than 200 %, - coated on one side with a pressure sensitive silicon adhesive of not more than 40 μm	S	New	UNDER EXAMINATION	UK	Applicant	Round 2018-07- PTFE tape is mainly used as a component in the manufacture of moulds for wind turbine blades.

3921 19 00	4656767/2017	Film [in the form of layers] containing by weight:  - 30 % or more but not more than 60 % of polypropylene (CAS RN 9003 07-0)  - 20 % or more but not more than 40 % of polyethylene (CAS RN9002-88-4)  - 20 % or more but not more than 40 % of boehmite (CAS RN 1318-23-6)  for use in the manufacture of lithium-ion batteries (1)	s	New	UNDER EXAMINATION	UK	Applicant	Round 2018-07 Used for the production of lithium-ion batteries
4016 99 57	4488695/2017	Pin boot of the brake caliper made of vulcanized rubber:  - with a diameter of 5 mm or more, but not more than 35 mm,  - with a height of 15 mm or more, but not more than 40 mm,  - with a ribbed design for use in the manufacture of goods of Chapter 87  (1)	S	New	UNDER EXAMINATION	SK	Applicant	ROUND 2018-07 Pin boot made of vulcanised rubber part of the brake caliper of a passenger car
5311 00 90	4609952/2017	Plain-woven fabric of paper yarns (imitation of jute) glued on tissue paper layer:  - weighing 230g/m² or more but not more than 280 g/m²,  - cut into rectangles with a side length of 40 cm or more but not more than 140 cm, of a kind used for laminating of decorative boxes	s	New	UNDER EXAMINATION	CZ	Applicant	ROUND 2018 Plain-woven fabric of paper yarns (imitation of jute) glued on tissue paper layer
5503 20 00	4613904/2017	Synthetic staple fibers, of polymers containing 98 % polyethylene terephthalate, for use in needle felt	s	New	UNDER EXAMINATION	BE	Applicant	ROUND 2018-07 Synthetic staple fiber for use in needle felt destined for filtration and sewage

		destined for filtration and sewage renovation						renovation
5603 14 90	4418530/2017	Non-woven fabrics of polyester microfibers, resulting from polyester fibers with uniform section, containing Polyethylene terephthalate not less than 74 % and weight more than 150 g/m2, with a denier ranging from 0.06 to 0.30 den	s	New	UNDER EXAMINATION	IT	Applicant	ROUND 2018-07 Non-woven fabrics of polyester microfibers
5911 90 99	4613955/2017	Loudspeaker vibration damper, made from round, corrugated, flexible and cut- to-size tissue of textile fibres of polyester, cotton or aramide or a combination hereof, of a kind used in car loudspeakers	S	New	UNDER EXAMINATION	BE	Applicant	ROUND 2018-07 Loudspeaker vibration damper, made from round, corrugated, flexible and cut-to-size tissue of textile fibres of polyester, cotton or aramide or a combination hereof, of a kind used in car loudspeakers
7326 90 92	4629002/2017	Forged steel nozzle shell with integral flange consisting in a piece issued from 4 castings, worked and machined - diameter 5 755 mm (+3mm margin) - height 3 453 mm (+1mm margin) - total weight 168 tons (+125 kg margins) of a kind used for the fabrication of a nuclear reactor vessel	s	New	UNDER EXAMINATION	FR	Applicant	ROUND 2018 Forged steel nozzle shell with integral flange
7326 90 98	4548037/2017	Surface-hardened, steel piston rod for a conventional shock absorber of motor vehicles:  - with a chrome coating,  - of a diameter of 11 mm or more, but not more than 28 mm,  - of a length of 80 mm or more, but not more than 600 mm, with a threaded end or a mandrel for resistance welding	S	New	UNDER EXAMINATION	PL	Applicant	ROUND 2018-07 Surface-hardened, steel piston rod for a conventional shock absorber of motor vehicles

7409 19 00	4610317/2017	Plates, rolls or sheets:	S	New	UNDER	AT	Applicant	ROUND 2018
7410 21 00		- with at least one layer of woven glass fibre, impregnated with a fireretardant artificial or synthetic resin with a glass transition temperature (Tg) of more than 130 °C as measured according to IPC-TM-650, method 2.4.25, - coated on one or both sides with a copper film with a thickness of not more than 3,2 mm, - and containing at least one of the following - poly(tetrafluoroethylene) (CAS RN 9002-84-0) - poly(oxy-(2,6-dimethyl)-1,4-phenylene) (CAS RN 25134-01-4) - epoxy resin having a thermal expansion of not more than 10 ppm in length and width and not more than 25 ppm in height for use in the manufacture of circuit boards (2)			EXAMINATION			Plates, rolls or sheets
7410 21 00	4548096/2017	Plates of any type of nonwoven fibre, laminated on each side with glass-fibre fabric and impregnated with epoxide resin:  - with dimensions of 1092 x 1245 mm,  - a thickness of 0,2 mm or more but not more than 3,2 mm,  - covered on one or both sides with copper foil with a maximum thickness of not more than 0,15mm, for use in the manufacture of circuit boards  (1)	S	New	UNDER EXAMINATION	PL AT	Applicant Opposed	ROUND 2018-07 Plates of any type of nonwoven fibre, laminated on each side with glass-fibre fabric and impregnated with epoxide resin

7413 00 00	4613981/2017	Loudspeaker centering ring, consisting of one or more vibration dampers and minimum 2 non-insulated cupper wires, therein woven or pressed, of the kind used in car loudspeakers	S	New	UNDER EXAMINATION	BE	Applicant	ROUND 2018-07 Loudspeaker centering ring, consisting of one or more vibration dampers and minimum 2 non-insulated cupper wires, therein woven or pressed, of the kind used in car loudspeakers
7606 12 99	4610371/2017	Plates and sheet of aluminium alloys containing by weight:  - 0,25 % or more but not more than 7 % of zinc, and  - 1 % or more but not more than 3 % of magnesium, and  - 1 % or more but not more than 5 % of copper, and  - not more than 1 % of manganese of a thickness of 6 mm or more, but not more than 210 mm, of a width of 500 mm or more and of a length of 500 mm or more, consistent with the material specifications ABS 5323, [for use in the manufacture of connectors] of a kind used in aerospace industry  (1)	S	New	UNDER EXAMINATION	AT	Applicant	ROUND 2018 Plates and sheet of aluminium alloys
7607 11 90	4613389/2017	Aluminium and magnesium alloy strip or foil:  - of an alloy conforming to standards 5182-H19 or 5052-H19,  - in rolls,  - of a thickness (tolerance - 0,006 mm) of 0,15 mm, 0,16 mm, 0,18 mm or 0,20 mm,  - a width (± 0,3 mm) of 12,5 mm, 15,0 mm, 16,0 mm, 25,0 mm, 35,0 mm, 50,0 mm or 356 mm,  - an outside coil diameter of minimum 1250 mm but not more than 1350 mm,  - an inside coil diameter of 300 mm	S	New	UNDER EXAMINATION	SE	Applicant	ROUND 2018-07 2017-09-15 (request): Aluminum and magnesium alloy strip or foil to be used for aluminum strips

		or 400 mm, and - a camber tolerance of not more than 0,5 mm/750 mm, - a flatness measurement: I-unit ±5, and - a tensile strength of more than (5182-H19) 365 MPa or (5052-H19) 320 MPa, - a proof strength of more than (5182-H19) 340 MPa, or (5052-H19) 300 Mpa, - an elongation A50 of more than (5182-H19) 3 % or (5052-H19) 2,5 % and, - with a chemical composition: (5182-H19) Mg=4-5 %, Si=0,17 %, Fe=0,24 %, Cu=0,08 %, Mn=0,37 %, Zn=0,16 %, Al= balance or (5052-H19) Mg=2,5-2,8 %, Si=0,10 %, Fe=0,24 %, Cu=0,08 %, Mn=0,07 %,						
8310 00 00	4639207/2017	Zn=0,13 %, Ti=0,08 % Al= balance respectively for the standards.  Sign-plates with outer layers of	S	NI	UNDER	UK	Applicant	Round 2018-07
6510 00 00	403720112011	aluminium composite panels and a polyethylene core of a thickness of 1.8mm or more but not more than 4,2 mm	S	New	EXAMINATION	OK	Аррисан	It is to be used as a name-plate or as a sign-plate
8409 99 00	4629095/2017	Two-way flow control valve with housing, with  - at least 5 but not more than 9 outlet holes with at least 0,110 mm but not more than 0,134 mm diameter,  - at least 640 cm3 / minute but not more than 805 cm3 / minute flow rate,  - at least 19 but not more than 300 MPa operating pressure	S	New	UNDER EXAMINATION	HU	Applicant	ROUND 2018-07 Two-way flow control valve with housing
8409 99 00	4629083/2017	Device for measuring the pressure and temperature of fuel, with	S	New	UNDER EXAMINATION	HU	Applicant	ROUND 2018  Device for measuring the pressure and

		<ul><li>a printed circuit,</li><li>at least 275 MPa internal tightness,</li><li>a connector with 4 pins</li></ul>						temperature of fuel
8409 99 00	4629031/2017	Flow-control valve - made of steel, - with an outlet hole with a diameter of at least 0.175 mm, but not more than 0.185 mm, - with an inlet hole with a diameter of at least 0.255 mm, but not more than 0.265 mm, - with chromium nitride coating, - with a surface roughness of RP 0.4	S	New	UNDER EXAMINATION	HU	Applicant	ROUND 2018 Flow-control valve
8409 99 00 8481 10 99	4629133/2017	Electromagnetic pressure-control valve - with a plunger, - with at least 275 mPa internal tightness, - with a plastic connector with 2 silver or tin pins	S	New	UNDER EXAMINATION	HU	Applicant	ROUND 2018 Electromagnetic pressure-control valve
8413 91 00	4629114/2017	Electromagnetic valve for quantity control with  - a plunger,  - DLC (Diamond-like carbon) coating,  - a solenoid with a of coil resistance of at least 2.6 ohm, but not more than 3ohm,  - a supply voltage of 12 V	s	New	UNDER EXAMINATION	HU	Applicant	ROUND 2018 Electromagnetic valve for quantity control
8481 10 99	4562503/2017	Pressure reducing valves in a brass case with:  - a length of not more than 18 mm (± 1 mm),  - a width of not more than 30 mm (± 1 mm),  of a kind used for incorporation in fuel delivery modules of motor vehicles	s	New	UNDER EXAMINATION	DE	Applicant	Round 2018-07 For industrial installation in fuel delivery modules

8504 50 95	4573416/2017	Self-induction coil with one or more windings, with an inductance per winding of not more than 62 mH, connected to one or more carrier materials, equipped with ferrites and at least one NTC resistor as a temperature sensor, whether or not with insulation covers, spacers and connection cables	s	New	UNDER EXAMINATION	DE	Applicant	Round 2018-07
8505 90 29	4629063/2017	Electromagnetic valve for quantity control  - with a solenoid with a coil resistance of at least 0.19 ohm, but not more than 0.52 omh, and with an inductance of at least 0.083 mH, but not more than 0,172 mH,  - with a supply voltage of 24 V,  - operating at a DC of at least 15.5 A, but not more than 16.5 A	s	New	UNDER EXAMINATION	HU	Applicant	ROUND 2018 Electromagnetic valve for quantity control
8506 50 30	4632204/2017	Lithium manganese dioxide battery, with:  - a diameter of 20 mm or more but not more than 25 cm  - a length of 0,30 mm or more but not more than 0,6 cm  - a voltage of 3 V or more but not more than 3,4 V  - a capacity of 200 mAh or more but not more than 600 mAh  - an automotive test temperature range of -40°C or more but not more than +125°C  for use as a component within the manufacture of Tyre Pressure Measuring Systems (TPMS)  (1)	S	New	UNDER EXAMINATION	UK	Applicant	ROUND 2018 Lithium manganese dioxide battery
8507 50 00	4631713/2017	Battery assy divided to 28 units that has dimensions of: - a length of 220 mm or more but not more than 280 mm,	S	New	UNDER EXAMINATION	TR	Applicant	ROUND 2018 Battery assy divided to 28 units

		<ul> <li>a width of 15 mm or more but not more than 25 mm,</li> <li>a height of 100 mm or more but not more than 150 mm,</li> <li>with the battery dimensions of:</li> <li>a length of 220 mm or more but not more than 280 mm,</li> <li>a width of 500 mm or more but not more than 600 mm,</li> <li>a height of 100 mm or more but not more than 150 mm,</li> <li>connectors for conneciton,</li> <li>rectangular battery cells,</li> <li>168 cells (28 units x 6 cells), between 190 and 210 nominal voltage for use in the manufacture of motor vehicles of Chapter 87</li> <li>(1)</li> </ul>						
8512 20 00	4490734/2017	Cabin overhead lamp of passenger car in plastic housing, for a voltage of 8 V or more but not more than 16 V, comprising:  - at least two light bulbs, - switch for turning on and off the light in the cabin, - whether or not emergency call button (E-Call), - whether or not ultrasonic intrusion protection (UIP), - whether or not switch for opening and closing of the panoramic roof for use in the manufacture of motor vehicles (1)	S	New	UNDER EXAMINATION	SK	Applicant	ROUND 2018-07 Cabin overhead lamp part of cabin of passenger car
8512 30 10	4490710/2017	Sound alarm device for protection against burglary into the vehicle  - with an operating temperature of – 45 °C or more, but not more than +	S	New	UNDER EXAMINATION	SK	Applicant	ROUND 2018-07 Sound alarm device for protection against burglary into the vehicle

		95 °C, - for a voltage of 9 V or more, but not more than 16 V, - in a plastic housing, - whether or not with a metal holder for use in the manufacture of motor vehicles (1)						
8529 90 92	4565277/2017	LCD modules combined with touch screen facilities:  - solely consisting of one or more TFT glass cells;  - with LCD panel diagonal measurement of 10,7 cm or more but not more than 31,2 cm;  - with backlight;  - with or without printed circuits boards with control electronics for pixel addressing only;  - without CAN (Controlled Area Network) controllers;  - without an EPROM memory;  - and not incorporating a motorised mechanism for moving the display screen; used for installation solely in the motor vehicles of chapter 87 (1)	S	New	UNDER EXAMINATION	PL	Applicant	ROUND 2018-07 LCD modules combined with touch screen facilities
8537 10 91	4488666/2017	Electronic control unit of automatic parking system with capability to evaluate the surroundings of the car and to control automatic parking:  - of a voltage of 5 V or more but not more than 16 V,  - with connector,  - in a plastic housing,  - whether or not with a metal holder for use in the manufacture of goods of Chapter 87	S	New	UNDER EXAMINATION	SK	Applicant	ROUND 2018-07 Electronic control unit of automatic parking system with capability to evaluate the surroundings of the car and to control automatic parking

8537 10 91	4490679/2017	(1)  Electronic control unit for optimal engine performance:  - with a voltage of 8 V or more but not more than 16 V,  - with at least one composite connector,  - in a metal housing,  - whether or not with metal holders for use in the manufacture of motor vehicles (1)	s	New	UNDER EXAMINATION	SK	Applicant	ROUND 2018-07 Electronic control unit for optimal engine performance part of engine compartment of passenger car
8537 10 98	4492452/2017	Electronic control unit of blind spot detection system  - with a voltage of 8 V or more but not more than 16 V,  - in a plastic housing,  - with cable and connector for use in the manufacture of motor vehicles  (1)	S	New	UNDER EXAMINATION	SK	Applicant	ROUND 2018-07 Electronic control unit of blind spot detection system
8537 10 98	4492411/2017	Electronic airbag control unit:  - with an operating temperature of – 45 °C or more, but not more than 90 °C,  - with a voltage of 8 V or more but not more than 16 V,  - with two connectors,  - in a metal housing for use in the manufacture of motor vehicles (1)	S	New	UNDER EXAMINATION	SK	Applicant	ROUND 2018-07 Electronic airbag control unit part of dashboard of passenger car
8540 91 00	4610399/2017	Thermionic electron source (emitter point) in a metal housing with electric connectors having  - a graphite carbon shield mounted	s	New	UNDER EXAMINATION	AT	Applicant	ROUND 2018 Thermionic electron source (emitter point) in a metal housing with electric connectors

		in a mini-Vogel type system - separate pyrolytic carbon blocks used as heating elements and - a cathode temperature of less than 1800 K at a filament current of 1,26 A [suitable for incorporation into a cathode ray tube for raster electron microscopes, semiconductor inspection systems or electron beam lithography devices]						
8708 40 20	4631667/2017	Transmission assembly which houses 3 other shafts inside it and offers a rotating switch for shift position, consisting of:  - cast aluminium body,  - differential gear,  - 2 electrical machines and gears, with the dimensions of:  - a width of 300 mm or more but not more than 350 mm,  - a height of 420 mm or more but not more than 500 mm,  - a length of 500 mm or more but not more than 600mm,  for use in the manufacture of motor vehicles of Chapter 87  (1)		New	UNDER EXAMINATION	TR	Applicant	ROUND 2018 Transmission assembly which houses 3 other shafts inside it and offers a rotating switch for shift position
8708 50 55	4488773/2017	Steel wheel hub with molded screws for attachment of the wheel to the chassis of passenger car, with one or more bearings, whether or not with ABS grid, for use in the manufacture of goods of Chapter 87 (1)	S	New	UNDER EXAMINATION	SK	Applicant	ROUND 2018-07 Steel wheel hub with molded screws part of wheel suspension of a passenger car
8708 95 99	4636980/2017	Gas generator formed by ignition chamber, propellent chamber, and gas flow chamber, with the inflator dimensions of:  - a weight of 170 g or more but not more than 225 g,  - a length of 91 mm or more but not	s	New	UNDER EXAMINATION	TR	Applicant	ROUND 2018 Inflator that generates gas flow by the mean of pyrotechnic technologies

			more than 135 mm, - a diameter of 25 mm or more but not more than 26 mm						
8714 99 10		4537684/2017	Bicycle handlebars, - with or without integrated stem, - made out of carbon fibers and synthetic resin, for use in the manufacture of bicycles (1)	S	New	UNDER EXAMINATION	DE AT	Applicant Co-applicant	Round 2018-07 for use in the manufacture of bicycles
ex 2823 00 00	10	294577/2011 446/2/1995	TR(15.09.2017) Amending request Titanium dioxide (TiO2) (CAS RN 13463-67-7) with minimum purity rate 98 % or more, particle size between 0,7 μm and 2,1 μm (Type: Anatase)	s	Amendment	UNDER EXAMINATION	AT	Applicant	Round 2018-07 TR- request for amendment prolong ex 2018 - "green list item"  ROUND 2014-07-01: A request for amendment of the existing text as follows:
			Titanium dioxide (CAS RN 13463-67-7): - of a purity by weight of 99,9 % or more, - with an average grain-size of 0,7 μm or more but not more than 2,1 μm						Titanium dioxide (CAS RN 13463-67-7):  — of a purity by weight of 99,9 % or more,  — with an average grain-size of 0,7 μm or more but not more than 2,1 μm
ex 2920 29 00	60	1279693/2016	DE request for amendment (2018-09-15): Requested: Fosetyl-sodium (CAS RN 39148-16-8) in form of an aqueous solution with a content by weight of fosetyl-sodium of 35 % or more but not more than 45 %	s	Amendment	UNDER EXAMINATION	DE	Applicant	ROUND 2018-07 request for amendment
			Fosetyl-sodium (CAS RN 39148-16-8) in form of an aqueous solution with a content by weight of fosetyl-sodium of 35 % or more but not more than 45 % for use in the manufacture of pesticides (1)						

ex 3208 90 19 ex 3208 90 91	25 20	312663/2012	Tetrafluoroethylene copolymer in butylacetate solution with a content of solvent of 50 % (± 2 %) by weight	s	Amendment	UNDER EXAMINATION	DE	Applicant	ROUND 2018-07: Amending request/ Classification issues prolong ex 2018 - "green list item"  Raw material for the manufacture of a water-based polymer-emulsion for leather
ex 3824 99 92	73	1997/5/2001	NL request for amendment (2017-09-15): Requested: $\alpha\text{-}(2,4,6\text{-Tribromophenyl})\text{-}\omega\text{-}(2,4,6\text{-tribromophenoxy})\text{poly[oxy(2,6\text{-dibromo-1,4-phenylene)isopropylidene(3,5\text{-dibromo-1,4-phenylene)oxycarbonyl]}} (CAS RN 71342-77-3)$	S	Amendment	UNDER EXAMINATION	BE	Applicant	ROUND 2018-07 request for amendment
			α-(2,4,6-Tribromophenyl)-ω-(2,4,6-tribromophenoxy)poly[oxy(2,6-dibromo-1,4-phenylene)isopropylidene(3,5-dibromo-1,4-phenylene)oxycarbonyl]						
ex 3824 99 96	74	1268378/2016	DE-Request for amendment (2017-09-15): Mixture with a non-stoichiometric composition:  - with a crystalline structure, - with a content of fused magnesia-alumina spinel and with admixtures of silicate phases and aluminates, at least 75 % by weight of which consists of fractions with a grain size of 1-3 mm and at most 25 % consists of fractions with a grain size of 0-1 mm - extended to fractions with a grain size of 0-1 mm and 1-3 mm in an indeterminate ratio, - extended by the fraction with a grain size of 3-6 mm or 0-50/60 mm	S	Amendment	UNDER EXAMINATION	PL AT	Applicant Opposed	request for amendment  ROUND 2017-07 rollover request  ROUND 2017 01:The material being the subject of this application is used in the production technologies of unburned magnesia-spinel-carbon refractory bricks and burned magnesia-spinel bricks employed in high-temperature processes in the industrial production

		Т	T		1	T	T		
			Mixture with a non-stoichiometric composition:  - with a crystalline structure, - with a content of fused magnesia-alumina spinel and with admixtures of silicate phases and aluminates, at least 75 % by weight of which consists of fractions with a grain size of 1-3 mm and at most 25 % consists of fractions with a grain size of 0-1 mm						
ex 3901 90 80	91	403/3/1982	Ionomer resin consisting of a salt of a copolymer of ethylene with methacrylic acid	S	Amendment	UNDER EXAMINATION	NL	Applicant	Round 2018-07 -Request for 0% duty rate (from 4%)
ex 3903 90 90	15	331267/2011	Copolymer in the form of granules containing by weight:  - 78 (± 4 %) of styrene,  - 9 (± 2 %) of n-butyl acrylate,  - 11 (± 3 %) of n-butyl methacrylate,,  - 1.5 (± 0,7 %) of methacrylic acid and  - 0,01 % or more but not more than  2,5 % of polyolefinic wax	S	Amendment	UNDER EXAMINATION	IE	Applicant	Round 2018-07- Amending request/ Classification issues
ex 3906 90 90	63	5451123/2016	DE request for amendment (2018-09-15):  Copolymer of methacrylic esters, butylacrylate and cyclic dimethylsiloxanes (CAS RN 143106-82-5)	S	Amendment	UNDER EXAMINATION	DE	Applicant	ROUND 2018-07 request for amendment
			Copolymer of (Dimethoxymethylsilyl)propyl methacrylate, butylacrylate, allyl						

					T			I	I
			methacrylate, methyl methacrylate and cyclosiloxanes (CAS RN 143106-82-5)						
ex 3912 90 10	10	1680/7/1996	DE request for amendment (2017-09-15): Cellulose acetate propionate, non- plasticised, in the form of powder: - containing by weight 25 % or more of propionyl (as determined by the ASTM D 817-72 method) and - of a viscosity of not more than 120 poise (as determined by the ASTM D 817-72 method)	s	Amendment	UNDER EXAMINATION	UK	Applicant	ROUND 2018 request for amendment
			Cellulose acetate propionate, non-plasticised, in the form of powder:  - containing by weight 25 % or more of propionyl (as determined by the ASTM D 817-72 method) and  - of a viscosity of not more than 120 poise (as determined by the ASTM D 817-72 method), for the manufacture of printing inks, paints, lacquers and other coatings, and reprographic coatings  (1)						
ex 3919 90 80	29	1089/2007 PROLONG 2015	NL request for amendment (2017-09-15):  Polyester, Polyethylene or Polypropylene film coated on one or both sides with an acrylic and/or rubber pressure sensitive adhesive, whether or not supplied with a release liner, put up in rolls of a width of 45,7 cm or more but not more than 160 cm	S	Amendment	UNDER EXAMINATION	ΙΈ	Applicant	ROUND 2018-07 NL request for amendment (2017-09- 15):
			Polyester film coated on both sides with an acrylic and/or rubber (pressure sensitive) adhesive put up in rolls of a						

			width of 45,7 cm or more but not more than 132 cm (supplied with a release liner)						
ex 3919 90 80 ex 9001 90 00	83 33	1159/2008	Reflector or diffuser sheets, in rolls, - for protection against ultraviolet or infra-red heat radiation, to be affixed to windows or - for equal transmission and distribution of light, intended for LCD modules	S	Amendment	UNDER EXAMINATION	PL	Applicant	Round 2018-07 - Amending request/Possible deletion of 3919 90 after decision from CCC
ex 3920 99 90	20	889/06	PL request for amendment (2018-09-15):  Anisotropic conductive film, in rolls, of a width of 1,2 mm or more but not more than 3,15 mm and a maximum length of 300 m, used for joining electronic components in the production of LCD or plasma displays.	s	Amendment	UNDER EXAMINATION	PL	Applicant	ROUND 2018-07 request for amendment (2018-09-15):
			Anisotropic conductive film, in rolls, of a width of 1,5 mm or more but not more than 3,15 mm and a maximum length of 300 m, used for joining electronic components in the production of LCD or plasma displays						
ex 3926 30 00 ex 8708 29 10 ex 8708 29 90	10 10 10	1233437/2015	NL(15.09.2017) Plastic cover with clips for the exterior rear-view, for use in the manufacture of vehicles of Chapter 87	s	Amendment	UNDER EXAMINATION	SK	Applicant	Round 2018-07:request for adding end use
			Plastic cover with clips for the exterior rear-view mirror of motor vehicles						
ex 3926 90 97 ex 8538 90 99	37 40	848226/2014	Polycarbonate control interface buttons for steering pad switches coated on the	S	Amendment	UNDER EXAMINATION	SK	Applicant	Round 2018-07 Request for amendment/adding end use

			outside with scratch resistant paint						
ex 3926 90 97	50	3082385/2013	Knob of car radio front panel, made of Bisphenol A-based polycarbonate	S	Amendment	UNDER EXAMINATION	HU	Applicant	ROUND 2018-07 Request for amendment/adding end use
ex 3926 90 97	77	5560026/2016	Silicone decoupling ring, with an inner diameter of 15,4 mm (+0,0 mm/-0,1 mm), of a kind used in car parking aid sensor systems	s	Amendment	UNDER EXAMINATION	FR	Applicant	Round 2018-07 Request for amendment/adding end use
ex 7604 29 10	40	826828/2014	AT- Amending request Bars and rods of aluminium alloys containing by weight:  - 0,25 % or more but not more than 7 % of zinc, and  - 1 % or more but not more than 3 % of magnesium, and  - 1 % or more but not more than 5 % of copper, and  - not more than 1 % of manganese consistent with the material specifications AMS QQ-A-225 or ABS5239, of a kind used in aerospace industry (inter alia conforming NADCAP and AS9100) and obtained by rolling mill process or by extrusion process  Bars and rods of aluminium alloys containing by weight:	S	Amendment	UNDER EXAMINATION	FR DE	Applicant Opposed	Round 2018-07 - Request for amendment ROUND 2015-01: are designated to be used in manufacture of certain components for aircrafts
			<ul> <li>0,25 % or more but not more than</li> <li>7 % of zinc, and</li> <li>1 % or more but not more than 3 % of magnesium, and</li> </ul>						
			- 1 % or more but not more than 5 % of copper, and - not more than 1 % of manganese consistent with the material specifications AMS QQ-A-225, of a kind used in						

					1		1		
			aerospace industry (inter alia conforming NADCAP and AS9100) and obtained by rolling mill process						
ex 8108 90 30	80	167191/2010 PROLONG 2016	AT- request for amendment: Titanium-aluminium-vanadium alloy (TiAl6V4) bars, rods and wire, complying with AMS standards 4928, 4965 or 4967	S	Amendment	UNDER EXAMINATION	DE	Applicant	Round 2018-07-amending request
			Titanium-aluminium-vanadium alloy (TiAl6V4) wire, complying with AMS standards 4928, 4965 or 4967						
ex 8301 60 00	20	589777/2010	Keypads of silicone or plastic,	S	Amendment	UNDER	AT	Applicant	ROUND 2018-07
ex 8413 91 00	40		- whether or not with parts of metal,			EXAMINATION		TT ···	Request for adding end-use
ex 8419 90 85	30		plastic, glass fibre reinforced epoxide						
ex 8438 90 00	20		resin or wood,						
ex 8468 90 00	20		- whether or not printed or surface						
ex 8476 90 90	20		treated,						
ex 8479 90 70	83		- whether or not with electrical						
ex 8481 90 00	30		conducting elements,						
ex 8503 00 99	70		- whether or not with keypads foil						
ex 8515 90 80	30		glued on the keyboard,						
ex 8536 90 95	95		- whether or not with protective foil,						
ex 8537 10 98	70		<ul> <li>single or multilayer</li> </ul>						
ex 8708 91 20	10								
ex 8708 91 99	20								
ex 8708 99 10	50								
ex 8708 99 97	40								
ex 8483 30 32	20	311427/2012	FR request for amendment (2017-09-13):	s	Amendment	UNDER	HU	Applicant	ROUND 2018-07
ex 8483 30 38	50		Bearing housing of a kind used in turbochargers:  of precision-cast grey cast iron complying with standard DIN EN 1561 or precision-cast ductile cast iron complying with DIN EN 1560, - with oil chambers,			EXAMINATION			request for amendment

		<ul> <li>without bearings,</li> <li>with a diameter of 50 mm or more, but not more than 250 mm,</li> <li>with a height of 40 mm or more, but not more than 150 mm,</li> <li>whether or not with water chambers and connectors</li> </ul>						
		Bearing housing of a kind used in turbochargers:  - of precision-cast grey cast iron complying with standard DIN EN 1561,  - with oil chambers,  - without bearings,  - with a diameter of 50 mm or more, but not more than 250 mm,  - with a height of 40 mm or more, but not more than 150 mm,  - whether or not with water chambers and connectors						
ex 8501 31 00 25	313124/2012	SK request for amendment (2017-09-15): DC motors, brushless, with:  - an external diameter of 80 mm or more, but not more than 200 mm,  - a supply voltage of 9 V or more, but not more that 16 V,  - an output at 20 °C of 300 W or more, but not more than 750 W,  - a torque at 20 °C of 2,00 Nm or more, but not more than 7,00 Nm,  - a rated speed at 20 °C of 600 rpm or more, but not more than 3 100 rpm,  - with or without the rotor angle position sensor of resolver type or Hall effect type, of the kind used in power steering systems for cars	s	Amendment	UNDER EXAMINATION	PL	Applicant	ROUND 2018-07 request for amendment

			DC motors, brushless, with:  - an external diameter of 80 mm or more, but not more than 100 mm,  - a supply voltage of 12 V,  - an output at 20 °C of 300 W or more, but not more than 750 W,  - a torque 20 °C of 2,00 Nm or more, but not more than 7,00 Nm,  - a rated speed at 20 °C of 600 rpm or more, but not more than 3 100 rpm,  - with or without the rotor angle position sensor of resolver type or Hall effect type, of the kind used in power steering systems for cars						
ex 8503 00 91 ex 8503 00 99	31 32	731/1/1996	PL(12.09.2017)-Amending request: Rotor, at the innerside provided with one or two magnetic rings (uniform or sectional) whether or not incorporated in a steel ring	s	Amendment	UNDER EXAMINATION	FR	Applicant	Prolongation Exercise 1/1/2014
			Rotor, at the innerside provided with one or two magnetic rings whether or not incorporated in a steel ring						
ex 8503 00 99	50	3081213/2013	PL(12.09.17) Request for text modification Stator for brushless motor, with:  - an internal diameter of 206,6 mm (± 0,5)  - an external diameter of 265,0 mm (± 0,2) and  - a width of 37,50 mm (-0,3) or more but not more than 47,50 mm (+ 0,3) of a kind used in the manufacture of washing machine, washer-dryer or dryer	S	Amendment	UNDER EXAMINATION	PL	Applicant	Round 2018-07 request for text modification

			equipped with direct drive drums  Stator for brushless motor, with:  - an internal diameter of 206,6 mm (± 0,5)  - an external diameter of 265,0 mm (± 0,2) and  - a width of 41,00 mm (± 0,3) of a kind used in the manufacture of washing machine, washer-dryer or dryer equipped with direct drive drums						
ex 8505 11 00	60	312685/2012	DE- Amending request Rings, tubes, bushings or collars made from an alloy of neodymium, iron and boron, with - an external diameter of not more than 45 mm, - a height of not more than 45 mm, of a kind used in the manufacture of permanent magnets after magnetisation	S	Amendment	UNDER EXAMINATION	DE	Applicant	Round 2018-07 - Text amendment
			Rings, tubes, bushings or collars made from an alloy of neodymium, iron and boron, with  - a diameter of not more than 45 mm,  - a height of not more than 45 mm, of a kind used in the manufacture of permanent magnets after magnetisation						
8526 91 20 8527 21 20 8527 29 00		1497716/2017	SE (14.06.2017): Integrated audio module (IAM) with a digital video output for connection to an external digital touch screen monitor and a digital driver information module (DIM), capable of being interfaced to other Electronic Control Units (ECUs) in the vehicle, capable of communicating	S	Amendment	UNDER EXAMINATION	SE ES	Applicant Opposed	Round 2018-07- Roll over request Round 2018-01- Objected The module will be mounted into cars during manufacturing

through Local Interconnect Network (
LIN), FlexRay, Media Oriented System
Transport (MOST), Ethernet, Low-
voltage differential signaling (LVDS) and
Automotive pixel link (APIX)
communication buses, with:
- A HD radio tuner,
- Satellite navigation function
dependent on Global Navigation
Satellite System (GNSS) positioning
signals,
- A Traffic Message Channel (TMC)
tuner,
- Satellite navigation functionality
with online traffic services,
- Ability to receive, process and
transmit information from climate
system, safety system and other
vehicle internal systems
- Phone services via USB or
Bluetooth hands-free,
- Services via third party
applications and online cloud services,
With or without:
- A CD and DVD drive
for the use in the manufacture of motor
vehicles of heading 8703
7
Integrated audio module (IAM) with a
digital video output for connection to an
external digital touch screen monitor and
a digital driver information module
(DIM), capable of being interfaced to
other Electronic Control Units (ECUs) in
the vehicle, capable of communicating
through LIN, FlexRay, MOST, Ethernet,
LVDS and APIX communication buses,
with:
- a HD radio tuner,
- satellite navigation function

ex 8529 90 92	55	816713/2014	dependent on Global Navigation Satellite System (GNSS) positioning signals,  - a Traffic Message Channel (TMC) tuner,  - satellite navigation functionality with online traffic services,  - phone services via USB or Bluetooth hands-free,  - services via third party applications and online cloud services, With or without:  - a CD and DVD drive for the use in the manufacture of motor vehicles of heading 8703  DE request for amendment (2017-09-15): OLED modules, consisting of  - one or more TFT glass or plastic cells, containing organic material,  - with or without combined touch screen facilities and  - one or more printed circuit boards with control electronics for pixel addressing, for use in the manufacture of TV sets and monitors or for use in the manufacture of vehicles of Chapter 87	Amendment	UNDER EXAMINATION	PL	Applicant	ROUND 2018-07 request for amendment
			OLED modules, consisting of one or more TFT glass or plastic cells, containing organic material, not combined with touch screen facilities and one or more printed circuit boards with control electronics for pixel addressing, for use in the manufacture of TV sets and monitors  (1)					

		<u> </u>							4
ex 8708 99 10 ex 8708 99 97	30 15	5524287/2016	SK amending request (2018-09-15): Holder of front radiator or intercooler whether or not with rubber cushioning for use in the manufacture of goods of Chapter 87	S	Amendment	UNDER EXAMINATION	SK	Applicant	ROUND 2018-07 request for amendment  Holder is mounted to the front module of a passenger car
			Current Front radiator holder whether or not with rubber cushioning for use in the manufacture of goods of Chapter 87 (1)						
ex 9013 80 90	20	726268/2014	DE request for amendment (2017-09-15): Electronic semiconductor micro-mirror in a housing suitable for the automatic printing of conductor boards, mainly consisting of:  - one or more microelectromechanical mirrors (MEMS) manufactured with semiconductor technology, with a drive arranged in three-dimensional structures on the semiconductor material,  - whether or not in a combination with one or more monolithic application-specific integrated circuits (ASIC), of a kind used for incorporation into products of Chapters 84-90 and 95		Amendment	UNDER EXAMINATION	DE	Applicant	ROUND 2018-07 request for amendment
			Electronic semiconductor micro-mirror in a housing suitable for the automatic printing of conductor boards, mainly consisting of a combination of:  - one or more monolithic application-specific integrated circuits (ASIC),						

|--|

<sup>(1)</sup> Suspension of duties is subject to end-use customs supervision in accordance with Article 254 of Regulation (EU) No 952/2013 of the European Parliament and of the Council of 9 October 2013 laying down the Union Customs Code (OJ L 269, 10.10.2013, p. 1)